/ ARCVES40

Arc Flash long jacket, APC 2, ATPV 40 cal/cm², ELIM 37 cal/cm²

See online technical sheet



/ Standards

- **EN ISO 11612:2015 (Flamme and heat)** : A1, A2, B1, C1, F1
- **EN1149 (Electrostatic property)** : EN1149-5
- **EN 61482:2** : APC 2 (7Ka)
- **EN 61482-1-1**
- **ATPV (cal/cm²)** : 40
- **ELIM (cal/cm²)** : 36
- **EN ISO 13688**
- **CE category** : Catégory 3

/ Use

For occasional operations; Switching operations to disconnect or open the network, on electrical installations with incident thermal energy up to 40 cal/cm².
Protection against thermal effects of an electric arc.

/ Advantages

- Loose fit for greater comfort and mobility
- The FR (flame retardant) properties of the garment are guaranteed for 50 washes
- Very good mechanical strength (abrasion and tear resistance)
- Double qualification according to ATPV and ELIM for OPEN ARC
- No metal parts (non-magnetic)
- Metal free
- ATPV protection level visible on garment
- Overlapping garments for optimum protection

Document not contractually binding, errors and omissions excepted

/ Technical specifications

- **Size :** S, M, L, XL, 2XL, 3XL, 4XL
- **Main color :** Grey
- **Workwear color :** Grey
- **Collar style :** Low blas collar
- **Fastening :** Zipper fastening, Adhesive tape, Flap
- **Cloth composition table :** Tissu - 87% cotton 12% nylon 1% antistatic fiber - bom-precision/2-layer, 340 gsm







/ Accessories

	Reference	Designation
	CRYOVEST	Thermoregulating vest against heat risk and heat stress

Document not contractually binding, errors and omissions excepted

/ Measurement table

Size	Measurement type	Value	Measurement unit
S	Chest	90-97	cm
M	Chest	98-105	cm
L	Chest	106-113	cm
XL	Chest	114-121	cm
2XL	Chest	122-129	cm
3XL	Chest	130-137	cm
4XL	Chest	138-145	cm

Document not contractually binding, errors and omissions excepted