WORKMASTER™ DIELECTRIC BOOTS **RESPIREX**[™]



An electrically insulating dielectric boot with an integral steel toe cap and vulcanized rubber sole for superior slip resistance. The Respirex Dielectric boot provides protection of up to 20kV over the complete boot for over 8 hours, and 35kV over the sole for 3 minutes.

Boot Shaft

Power Generation

- · Yellow dielectric compound shaft
- 200 Joule Epoxy coated Steel toe cap to EN ISO 20345
- Seamless construction •
- · Kick off lug
- Extra shin protection
- · Adjustable height
- Ankle guard
- · Non-wicking knitted nylon lining
- · Comfort insole (removable and machine washable)
- REACH Compliant

Boot Sole

- Blue vulcanized rubber sole for maximum grip 30% better than a conventional safety boot sole
- Slip resistance performance twice that required by EN 13287 SRA and SATRA TM144 standards
- Cleated outsole for maximum grip
- Two to three times the wear resistance of conventional soles
- · Fuel and oil resistant
- · Greater cut resistance than conventional soles
- Resistance to hot contact 60 seconds 300°C.
- · Energy absorbing tunnel system conforms to EN 20345 E
- Cold insulation to EN ISO 20345 ٠

Care

- Machine washable at up to 40°C
- · Shelf life of over 10 years

Electrical Protection

Complete boot:	20 kV8 hours no damage 5 kV<5mA Leakage current
Sole:	35 kV3 minutes no damage

Certification

Safety Footwear	EN ISO 20345:2011
	- SB E CI HRO SRA FO
Electrically Insulating Footwear	EN 50321:1999 Class 0
	prEN 50321:2013 Class 2

Dielectric Footwear ASTM F1117 Personal Protective Equipment PPE DIR 89/686/EEC

Sizes

UK	3	4	5	6	7	8	9	10	11	12	13	14	15
EU	35	36	37	39	41	42	43	44	45	46	47	49	50
US	4	5	6	7	8	9	10	11	12	13	14	15	16

Specifications, configurations and colours are subject to change without notice.

C: www.respirexinternational.com : +44 (0)1737 778600

☑: info@respirex.co.uk



Respirex International Limited Unit F, Kingsfield Business Centre, Philanthropic Road, Redhill, Surrey, RH1 4DP, United Kingdom